

# PRODUCT ECO-DECLARATION

Product Name: NOKIA 31

Type of product: Machine-to-Machine GSM Connectivity Terminal

Mass (g) 65 g

Dimensions: 84 x 53 x 26 mm, 116 cc

### 1. MATERIAL USE

The product does not contain<sup>1</sup>:

- Asbestos
- Beryllium oxide
- Cadmium
- Chloroparaffins with chain length 10-13 C atoms, chlorination greater than 50%
- Lead in mechanical plastic parts
- Mercury
- Ozone depleting substances, according to those categories that are already banned in the Montreal protocol
- Polybrominated Biphenyls (PBB) or Polybrominated Diphenyl Ethers (PBDE) in Printed Wiring Boards and mechanical parts
- Polychlorinated Biphenyls (PCB) or Polychlorinated Terphenyls (PCT)

Electrical cable insulation material specification: PVC

#### 2. NOKIA PACKAGING AND DOCUMENTATION

The product packaging material does **not** contain heavy metals according to <u>94/62/EC</u>.

The product packaging does not contain Halogenated polymers (e.g. PVC).

The user guide is printed on non-Chlorine bleached paper.

Plastic packaging material is marked according to DIN 6120, ISO 11469 and ISO 1043-1 to -4.

#### 3. DISASSEMBLY AND RECYCLING

All mechanical plastic parts have material codes in accordance with ISO 11469 and ISO 1043-1 to -4 where practical to facilitate plastics recycling.

Whenever disposing of the product, its parts, packaging or battery, please use correct local disposal methods.

<sup>&</sup>lt;sup>1</sup> In levels more than 100 PPM by weight in the product



27-07-2004

# 2(2)

# NOKIA

# 4. ENERGY CONSUMPTION

The information below is given for the following power supply:

Charger: ACW-5

The average power consumption of the terminal without application board:

150 mW Standby: Maximum RF output: 3.65 W

Nokia is a signatory of the "EU Code of Conduct" efficiency of external power supplies for electronic and electrical appliances.

This information is based on scientific analysis and/or data provided by suppliers. There may be some variance in the information.